



Performance Criteria



Manufacturer: Sundance
Model: B20CC Inshore
Hull Type: Fiberglass
Test Date: September 13, 2006
Mfg. Address: Blackshear, GA

Test Data

RPM	MPH	GPH	MPG
Idle	-	-	-
1000	3.4	.4	8.5
1500	5.1	.6	8.5
2000	6.5	1.2	5.4
2500	7.6	1.6	4.8
3000	10.1	2.5	4.0
3500	15.3	3.7	4.1
4000	22.2	4.0	5.6
4500	27.1	6.1	4.4
5000	31.6	7.2	4.4
5500	34.6	8.4	4.1
5700 (WOT)	36.3	8.7	4.2

Length:	19' 10"
Beam:	7' 10"
Weight:	1,695 lbs
Max HP:	135 hp
Fuel Capacity:	33 gal

Power: Single BF90

Horsepower:	90
Displacement:	1.5 L
Weight:	359 lbs.
Gear Ratio:	2.33:1
Mounting Height:	3 rd Hole
Prop (Material/Blades)	Stainless (3)
Prop Manufacturer	Solas
Prop (Diameter/Pitch)	13 7/8 x 15

Test Conditions

No. of People:	2
Fuel Load:	33 gal
Total Weight:	2,275 lbs
Air Temperature:	78°
Test Conditions	Calm
Elevation:	800'
Wind Velocity:	0-5 mph

Data may vary due to changes in weather, elevation and load conditions. Speed data gathered by GPS receiver.

Time to Plane: Seconds

Acceleration 0~15 MPH: 5.85 Seconds