



# Performance Criteria



**Manufacturer:** Triton  
**Model:** 2300 Walkaround  
**Hull Type:** Fiberglass  
**Test Date:** June 9, 2001  
**Mfg. Address:** 15 Bluegrass Drive  
 Ashland City, TN 37015

## Test Data

RPM	MPH	GPH	MPG
Idle	-	-	-
1000	6.5	2.4	2.7
1500	8.4	4.5	1.87
2000	9.3	9.3	1.00
2500	14.9	16.2	.92
3000	22.0	21.3	1.03
3500	30.2	25.5	1.19
4000	35.6	28.2	1.26
4500	40.7	32.4	1.26
5000	45.4	44.1	1.02
5500	48.3	52.5	.92
6000 (WOT)	54.0	60.9	.89

Length:	34' 10"
Beam:	10' 0"
Weight:	8,000 lbs
Max HP:	900 hp
Fuel Capacity:	355 gal

## Power: Triple BF225s

Horsepower:	225
Displacement:	3.5 L
Weight:	589 lbs.
Gear Ratio:	1.86:1
Mounting Height:	2 <sup>nd</sup> Hole
Prop (Material/Blades)	Stainless (3)
Prop Manufacturer	Power Tech OFS
Prop (Diameter/Pitch)	15 ¼ x 19

## Test Conditions

No. of People:	2
Fuel Load:	
Total Weight:	12,175 lbs
Air Temperature:	
Test Conditions	
Elevation:	
Wind Velocity:	

Data may vary due to changes in weather, elevation and load conditions. Speed data gathered by GPS receiver.

Time to Plane: Seconds

Acceleration 0~20 MPH: Seconds