

HONDA MARINE

Performance Report



Stabicraft
345 Bluff Highway
Invercargill, New Zealand 9812

www.stabicraft.com

2023 Stabicraft 2500 Ultra Cab XL

Material:	Aluminum
Length:	25'
Beam:	8'5"
Weight w/o Engine:	3593 lbs.
Max HP:	400
Fuel Capacity in Gallons:	100
Transom Height:	30"
Steering:	Hydraulic
Jack Plate:	No
Mounting Hole:	#3

Test Conditions

Elevation (ft):	59
Wind Velocity (mph):	6
Air Temperature (°F):	85
Water Conditions:	Calm
Fuel Load in Gallons:	65
Number of People:	3

Propeller

Honda Lexor Plus	
Material:	Stainless Steel
Diameter/Pitch:	16 x 18
No. of Blades:	3
Part Number:	58130-ZVPA-C011-M1
Prop Vent Hole:	NA

Performance Data

RPM	MPH	GPH	MPG	RANGE*
650	3.28	0.66	4.94	444.95
1000	6.09	1.27	4.80	431.57
1500	7.87	2.23	3.53	317.71
2000	9.97	3.44	2.89	260.52
2500	15.34	5.42	2.83	254.56
3000	22.51	6.76	3.33	299.81
3500	28.53	8.74	3.26	293.75
4000	34.53	12.59	2.74	246.89
4500	38.31	16.37	2.34	210.62
5000	43.84	20.46	2.14	192.89
5500	47.81	26.62	1.80	161.68
6000	50.79	31.11	1.63	146.92
6005	50.82	31.11	1.63	147.02

Acceleration (0-20 MPH) - 4.7 Seconds

* - Fuel range (Miles) data based on 90% of fuel capacity

***Testing was completed using Pre Production engines**

Engine

Honda BF350A

Engine Type:	60° V-8 VTEC
Horsepower:	350
Displacement:	5.0L
Operating Range:	5000-6000
Weight:	754
Gear Ratio:	1.79:1
Control Type:	IST



Data presented should be used as a guide. Actual results may vary due to changes in weather, water conditions, elevation and load. Honda reserves the right to change the specifications on this report or it's engines without notice

© 2023 American Honda Motor Co., Inc



The best warranty in the business.

Only Honda gives you a full, five years, non-declining warranty.

No strings. No catches. It's that simple.

