HONDA MARIDE

Performance Criteria



| RPM | MPH | GPH | MPG |
|------|------|-----|------|
| Idle | 2.8 | | |
| 1000 | 4.3 | .6 | 7.17 |
| 1500 | 6 | 1 | 6 |
| 2000 | 7.5 | 1.5 | 5 |
| 2500 | 8.9 | 2.3 | 3.87 |
| 3000 | 13.4 | 3 | 4.47 |
| 3500 | 23.3 | 3.7 | 6.30 |
| 4000 | 27.6 | 4.7 | 5.87 |
| 4500 | 31.6 | 6.1 | 5.18 |
| 5000 | 34.7 | 7.9 | 4.39 |
| 5500 | 38.2 | 10 | 3.82 |
| 6000 | 42.5 | 13 | 3.27 |

Manufacturer: Arima Model: Sea Ranger 19

Mfg. Address: 47 37th Street

Auburn, WA 98002

| Length: | 18' 11" |
|----------------|------------|
| Beam: | 8' |
| Weight: | 1,650 lbs. |
| Max HP: | 150 |
| Fuel Capacity: | 48 gal. |

Power: Single BF135

| Horsepower: | 135 |
|------------------------|----------------------|
| Displacement: | 2.4 L |
| Weight: | 478 lbs. |
| Gear Ratio: | 2.14:1 |
| Mounting Height: | 2 nd Hole |
| Prop (Material/Blades) | Stainless (3) |
| Prop Manufacturer | PowerTech |
| Prop (Diameter/Pitch) | 15 ¼ x 17 |

Test Conditions

| No. of People: | 2 |
|------------------|------------|
| Fuel Load: | 20 gal. |
| Total Weight: | 2,602 lbs. |
| Air Temperature: | 45° |
| Test Conditions | Breezy |
| Elevation: | 20' |
| Wind Velocity: | 5-10 mph |

Data may vary due to changes in weather, elevation and load conditions. Speed data gathered by GPS receiver.

Time to Plane: 3.76 Seconds

Acceleration 0~20 MPH: 5.75 Seconds