



# Performance Criteria



**Manufacturer:** Bennington  
**Model:** 2250 RFS  
**Hull Type:** Pontoon  
**Test Date:** September 26, 2003  
**Mfg. Address:** Elkhart, IN

## Test Data

| RPM        | MPH  | GPH | MPG |
|------------|------|-----|-----|
| Idle       | -    |     |     |
| 1000       | 3.8  |     |     |
| 1500       | 5.4  |     |     |
| 2000       | 7.3  |     |     |
| 2500       | 9.5  |     |     |
| 3000       | 16.2 |     |     |
| 3500       | 20.3 |     |     |
| 4000       | 24.9 |     |     |
| 4500       | 29.4 |     |     |
| 5000       | 33.8 |     |     |
| 5500       | 37.4 |     |     |
| 5800 (WOT) | 38.7 |     |     |

|                |           |
|----------------|-----------|
| Length:        | 22' 0"    |
| Beam:          | 8' 6"     |
| Weight:        | 2,200 lbs |
| Max HP:        | 175 hp    |
| Fuel Capacity: | 20 gal    |

**Power:** Single BF150

|                        |                      |
|------------------------|----------------------|
| Horsepower:            | 150                  |
| Displacement:          | 2.4 L                |
| Weight:                | 485 lbs.             |
| Gear Ratio:            | 2.14:1               |
| Mounting Height:       | 2 <sup>nd</sup> Hole |
| Prop (Material/Blades) | Stainless (3)        |
| Prop Manufacturer      | Powertech<br>OFS     |
| Prop (Diameter/Pitch)  | 15 ¼ x 17            |

## Test Conditions

|                  |           |
|------------------|-----------|
| No. of People:   | 2         |
| Fuel Load:       |           |
| Total Weight:    | 3,317 lbs |
| Air Temperature: |           |
| Test Conditions  |           |
| Elevation:       |           |
| Wind Velocity:   |           |

Data may vary due to changes in weather, elevation and load conditions. Speed data gathered by GPS receiver.

Time to Plane: Seconds

Acceleration 0~20 MPH: Seconds