

Performance Criteria





Test Data

RPM	MPH	GPH	MPG
Idle	-	-	-
1000	4.6	1.8	2.56
1500	6.6	3.2	2.06
2000	9.1	4.6	1.98
2500	14.1	9.0	1.57
3000	20.3	10.4	1.95
3500	23.1	15.2	1.52
4000	33.9	21.2	1.60
4500	39.4	26.8	1.47
5000	45.3	32.0	1.42
5500 (WOT)	47.8	38.0	1.26

Manufacturer: Everglades

Model: 290 Pilot

Hull Type: Fiberglass

Test Date: February 17, 2005 **Mfg. Address:** 544 Air Park Road

Edgewater, FL 32132

Length:	28' 7"
Beam:	9' 9"
Weight:	5,500 lbs
Max HP:	600 hp
Fuel Capacity:	200 gal

Power: Twin BF225s

Horsepower:	225
Displacement:	3.5 L
Weight:	589 lbs.
Gear Ratio:	1.86:1
Mounting Height:	4 th Hole
Prop (Material/Blades)	Stainless (3)
Prop Manufacturer	Solas Lexor
Prop (Diameter/Pitch)	15 ¼ x 19

Test Conditions

No. of People:	2
Fuel Load:	
Total Weight:	8,670 lbs
Air Temperature:	
Test Conditions	
Elevation:	
Wind Velocity:	

Data may vary due to changes in weather, elevation and load conditions. Speed data gathered by GPS receiver.

Time to Plane: Seconds

Acceleration 0~20 MPH: Seconds